



### FEATURES

- Die-formed cold-rolled steel wit poeder coated paint
- 100V~240 Input ,50/60Hz
- 120°degree beam angle even lighting distribution
- Ambient temperature:-20°C to 40°C
- 3 year limited warranty

### BENEFITES

- Ideal replacement for traditional incandescent surface mount fixture
- Excellent performance give the same light quality and brightness as incandescent surface mount fixture
- Provide high efficient and uniform lighting
- No UV IR radiation
- Excellent color consistency

### SPECIFICATIONS

Model	Power	Dimension	Input	Lumens	CCT	CRI	PF	Material	Life Span
CLE01R-2512	12W	10 inch Φ200mm	100-240V	840lm	3000K~6500K	>80	>0.9	PS/PMMA+SPCC	30000H/50000H
CLE01R-3018	18W	12 inch Φ250mm	100-240V	1260lm	3000K~6500K	>80	>0.9	PS/PMMA+SPCC	30000H/50000H
CLE01R-3524	24W	14 inch Φ300mm	100-240V	1680lm	3000K~6500K	>80	>0.9	PS/PMMA+SPCC	30000H/50000H
CLE01R-5830	30W	23 inch Φ300mm	100-240V	2100lm	3000K~6500K	>80	>0.9	PS/PMMA+SPCC	30000H/50000H

## Ceiling Light

