



可选配件 | OPTIONAL



名称：防坠措施  
材质：φ1.6多股防锈铁丝  
用途：高空安装时的防坠安全措施

详细参数 | DETAILED PARAMETERS

规格	产品型号	额定功率	光源数量	输入电压	控制方式	灰阶	角度区间	光通量	光源种类
单色常亮	TGBA-S1-120W	120W	6W*28PCS	AC220V	OFF/ON	—	18°-60°	10800LM	SMD5050
	TGBA-M1-150W	150W	6W*36PCS	AC220V	OFF/ON	—	18°-60°	13500LM	SMD5050
	TGBA-L1-200W	200W	6W*48PCS	AC220V	OFF/ON	—	18°-60°	18000LM	SMD5050
	TGBA-XL1-240W	240W	6W*56PCS	AC220V	OFF/ON	—	18°-60°	21600LM	SMD5050
	TGBA-XXL1-300W	300W	6W*72PCS	AC220V	OFF/ON	—	18°-60°	27000LM	SMD5050
	TGBA-XL2-480W	480W	6W*112PCS	AC220V	OFF/ON	—	18°-60°	43200LM	SMD5050
	TGBA-XXL2-600W	600W	6W*144PCS	AC220V	DMX512	—	18°-60°	54000LM	SMD5050
单色外控	TGBA-M1-D150W	150W	10W*28PCS	AC220V	DMX512	65536	5°-60°	14250LM	SMD5050
	TGBA-L1-D200W	200W	10W*36PCS	AC220V	DMX512	65536	5°-60°	19000LM	SMD5050
	TGBA-XL1-D240W	240W	10W*42PCS	AC220V	DMX512	65536	5°-60°	22800LM	SMD5050
	TGBA-XXL1-D300W	300W	10W*56PCS	AC220V	DMX512	65536	5°-60°	28500LM	SMD5050
	TGBA-XL2-D480W	480W	10W*84PCS	AC220V	DMX512	65536	5°-60°	45600LM	SMD5050
TGBA-XXL2-D600W	600W	10W*112PCS	AC220V	DMX512	65536	5°-60°	57000LM	SMD5050	
RGBW外控	TGBA-M1-RGBW210W	150W+60W	10W*28PCS	AC220V	DMX512	65536	10°-60°	—	SMD5050 4in1
	TGBA-L1-RGBW280W	200W+80W	10W*36PCS	AC220V	DMX512	65536	10°-60°	—	SMD5050 4in1
	TGBA-XL1-RGBW340W	240W+100W	10W*42PCS	AC220V	DMX512	65536	10°-60°	—	SMD5050 4in1
	TGBA-XXL1-RGBW420W	300W+120W	10W*56PCS	AC220V	DMX512	65536	10°-60°	—	SMD5050 4in1
	TGBA-XL2-RGBW680W	480W+200W	10W*84PCS	AC220V	DMX512	65536	10°-60°	—	SMD5050 4in1
	TGBA-XXL2-RGBW840W	600W+240W	10W*112PCS	AC220V	DMX512	65536	10°-60°	—	SMD5050 4in1

备注：①光通量基于4000K色温 ②以上角度全指半角

